

COAX diEci

DCX 170.3 100W

Compact **SIZE**



Technical Specifications

Component	-	Two way coaxial
Woofer size	mm (in.)	170 (6.7)
Tweeter size	mm (in.)	15 (0.6)
Power handling	W peak	100
	W continuous	50
Impedance	Ω	4
Frequency response	Hz	60 ÷ 21k
Sensitivity	dB SPL	93
Magnet size D-d-h	mm (in.)	80 x 32 x 10 (3.1 x 1.3 x 0.4)
Woofer voice coil \varnothing	mm (in.)	25 (1.0)
Woofer magnet	-	High density flux ferrite
Tweeter magnet	-	Neodymium
Woofer cone	-	Water-repellent pressed paper
Tweeter dome	-	PEI
Weight of one component	kg (lb.)	0,56 (1.23)

1. Shallow profile for an easy replacement of factory speakers.
2. Pure copper voice coil, wound on conex former, for maximum lightness.
3. Water-repellent treated paper cone.
4. TPU surround, for wide excursion and resonance damping.
5. Neodymium tweeter with PEI dome, for compactness and energy at high frequencies.
6. DIN size basket protected by abrasion-proof dust paint.
7. Tin-plated, high current terminals.
8. Silver-plated lead wires for maximum reliability and conductivity.
9. Epoxy glue for basket and motor system provides perfect coupling.
10. Low carbon content plates for maximum magnetic permeability and high heat dissipation.

Electro-Acoustic Parameters

D	mm	133
Xmax	mm	2
Re	Ω	3,6
Fs	Hz	85
Le	mH @ 1 kHz	-
Le	mH @ 10 kHz	-
Vas	l	11,3
Mms	g	8,8
Cms	mm/N	0,4
BL	T·m	3,7
Qts	-	0,95
Qes	-	1,21
Qms	-	4,39
Spl	dB	93

